

UKAS MANGERENT



- Lightweight and Easy to Work
- East Installation and Clean Site
- Thermal, Sound and Fire Resistance

SCG International India Pvt. Ltd

Unit No. 609, 6th Floor, The Palm Spring Plaza Golf Course Road Gurugram, Haryana, India 122001

Tel (IN) : +91 124 400 6413 Web : www.zmartbuild.com E-mail :scgindia@scg.com



ZMARTBULLD

• Environmentally-Friendly and Energy Saving

ZMARTBUILD WALL PANEL

2

BUILD WALL PANEL Hand Bo

ZMARTBUILD WALL PANEL are lightweight, steel reinforced, groove & tongue panels that can be easily installed by your normal on-site installers. They are suitable to be used as both external and internal walls.

> • Non-combustible : up to four hour fire rating

• Outstanding thermal and acoustic insulation qualities increase levels of comfort and save on energy cooling costs

 General installers can install ZMARTBUILD WALL PANEL of more than 30 sq.m. with 3 Labour team per day

• Steel reinforcing is specially coated to prevent corrosion and provides maximum durability

3

Product Specification

Specification


Dry Density


Working Density

Wind Load

Compressive Strength

Water Absorption







8 **BUILD WALL PANEL Hand Bo**



Use lever to lift ZMARTBUILD WALL PANEL until top of the panel reach the upper floor then insert a wood wedge under the panel.





Use steel angle to fasten the panel with floors on both upper and lower side of the panel by using steel plugs and screws.



8







Apply thin-bed mortar on side of the first panel then lift the next wall panel to attach and do the same as the previous steps.










Measure the gap and cut the last panel to fit in then install it in place.

11 sand-cement mortar.



ZMARTBUILD WALL PANEL Hand Book

9

Continue install wall panels until the gap can be



Fill the gap under the panels with



Fill all gaps between each panel with thin-bed mortar, wait until the mortar dry then rub with sandpaper #400.

10 TBUILD WALL PANEL Hand Boo

Finishing all gaps again with skim coat then rub 13 with sandpaper #200.



Finish ZMARTBUILD WALL PANEL Installation

14

Cautions

- Use for installating wall panel only. Please follow the steps in installation guide. Do not use wall panel as load bearing structure.
- Do not eat or breathe dust from cutting the product.
- ZMARTBUILD WALL PANEL are designed and instructed to use for wall partition only.

How to move **ZMARTBUILD WALL PANEL**

There is no obstruction besides of the truck.

1







11





2

Check the conditions of the packaging to make sure that it will not fail while being lifted in the air.

Insert soft belts under pallets at the designed positions.

3

4

Lift wall panel to the loading area and then use hand lift to move wall panel into the building.

SAFETY FIRST

PROJECT REFERENCE

CAUTIONS

ZMARTBUILD WALL PANEL

Installation procedures

manual.

To transfer panels



Move the pallet by using hand lift or fork lift and check the packaging before moving. Pallet strap is tight Pallets must be in good condition.

Move one pallet at a time.

Pallets must be in good condition.

Beware of falling objects when moving

order to reduce muscle injuries.

☑ Lift the product with the right manner in

☑ It is required at least 2 persons to lift the product. **Do not throw or bump the product in order to** prevent product damage and injuries.

packaging before moving.

Move one pallet at a time.

Move the pallet by workers.

✓ Pallet strap is tight

☑ Do not move pallet on sloping areas over 36 degrees and rough area to prevent fall.

Move the pallet by using crane and check the





Avoid keeping the products outdoors over 30 days in order to prevent deterioration of packaging from humidity and weather.



Stack packs no higher than two packs height or no higher than 1.7 m. to prevent falling.

It is required at least 2 persons to

install ZmartBuild Wall Panel. Study

andfollow the technical installation



SAFETY

Wear standard personal protective equipment (PPE) e.g. dust mask, safety glasses, safety work clothes, work gloves, safety shoes and helmet. If dust gets in eyes, don't rub your eyes. Rinse cautiously with water for several times. If eyes irritation persists, get medical advice/attention.

How to use

Wall panel is suitable to be used for non-load bearing wall for both external and internal walls. Install wall panel by using specific tools and equipment for autoclaved lightweight oncrete only.


Product Description

ZMARTBUILD WALL PANEL is an autoclaved lightweight concrete with reinforced steel. The steel is coated with rust protection.

SCG International India Pvt. Ltd

Unit No. 609, 6th Floor, The Palm Spring Plaza, Golf Course Road, Gurugram, Haryana, India, 122001 **ZMARTBUILD Call Center :** Tel (IN) : +91 124 400 6413

Web : www.zmartbuild.com







HOSPITAL


UILD WALL PANEL Hand Book

Various Application of ZMARTBUILD WALL PANEL

- Cladding for heat protection
- Horizontal Installation
- Till Mount Installation



Bangkok Hospital Chiang Rai



ZMARTBUILD WALL PANEL Hand Book

HOUSING



Rameshwaram Residency | India



Tassanee Village



Jakpaisarn Village



Puno Adventure Arena | India



Viva City Mall | India



Siam Paragon



Terminal 21 Korat