



*** Note**

- *1 SCG Smartboard 8, 10, 12mm. thick, choosing appropriate work
- *2 SCG self drilling wing screw 13 mm.
- *3 For SCG Smartboard 3.5–8 mm. thick, using SCG Needle point screw 23 mm. fix on steel frame 0.55–0.80 mm. thick.
For SCG Smartboard 6–12 mm. thick, using SCG self drilling wing screw 32 mm. fix on steel frame 1.2–3.2 mm. thick.
- *4 For No Space lining solution, using steel frame thickness at least 0.55 mm., width at least 38 mm.
For space lining solution using steel frame thickness at least 0.55 mm., width at least 42 mm.
If steel frame thickness size is less than aforementioned size, should add frame more (Double frame)
- *5 Painting by Acrylic paint 100% for external or covering by other decorative material such as wall paper

DIMENSIONS...MM.	NAME	DATE	◀ ⊗	SCALE : NOT TO SCALE	PAGE : 8/13
DRAWN : .RATTHACHART Y.		22/04/2557		Installation of SCG Smartboard with steel stud (external wall)	
DESIGNED : .DEJA W.		.			
CHECKED : .DEJA W.		.			
APPROVED : .BODIN D.		.			
CANCEL DWG.NO. : .		.			
REFER DWG.NO. : .	DIR/FILE :		<div style="display: flex; justify-content: space-between; align-items: center;"> SCG Smartboard </div>		
CEMENT-BUILDING MATERIALS CO.,LTD.					