

S-1 MULTIPURPOSE

Silicone sealant (Neutral)

S-1 MULTIPURPOSE is a one component of neutral moisture curing silicone sealant that curing at room temperature. It is suitable for various building material tile, aluminum, glass, wood, edge of door and window, or other sealing applications.

FEATURES

- Excellent bonding adhesion
- Good Elongation
- Excellent weather resistance
- Antifungal Properties
- Fast curing at room temperature
- Odorless of Acetic Acid
- Non shrinkage

APPLICATIONS

- Ceramic Tile
- Glass
- Brick
- Cement
- Aluminium
- Fiberglass
- Painted Finished
- Wood

TECHNICAL DATA

Item	Standard	SPEC	S-1 MULTIPURPOSE
Tack Free Time : min	-	10 - 15	12
Tensile Strength : MPa	ISO 37	0.8 - 1.2	1.05
Elongation at break : %	ISO 37	400 - 600	530
Bonding Strength (3 Days) : MPa * Tile - Tile	-	0.1 - 0.3	0.20
Shore A hardness	ASTM C 661	25 - 30	27

INSTRUCTION

- Cut the tip of cartridge, and cut nozzle at 45 degree angle.
- Insert cartridge into caulking gun and apply it into the joint with completely fill.
- Smooth bead with tooling for the best appearance while their fresh.
- Surface will be dried 10 min and leave area before use 24 hour.



RECOMMENDATION FOR USE


- For the best result, finish the whole cartridge after opened. Remaining in the cartridge, keep it tightly and avoid moisture in atmosphere.
- One year after manufacturing date when stored unopened in dry.
- 12 m. / cartridge, dimensions of nozzle 5 mm.


PACKAGING

- 300 ml. / cartridge
- 30 cartridges / box

COMPANY CONTACT

Noritake SCG Plaster CO., LTD.
 32 Moo7, Nongplakradi Road,
 Nongpling, Nongkhae District,
 Saraburi 18140 THAILAND

 +66 36 373578 – 82

 +66 36 373577

Website : www.noritake-scg.com

COLOR

