

# ULTRA FLEX

Polyurethane adhesive

**ULTRA FLEX** is polyurethane elastic adhesive with excellence flexibility suitable for wood flooring metal-gypsum board , metal-fiber cement board repair wall cracking , jointing between concrete slabs.

## FEATURES

- 400% Elongation
- Weather resistance
- Paintable
- Non shrinkage
- Non bubble
- Isocyanate and solvent free

## APPLICATIONS

- Wood flooring
- Metal-gypsum board
- Metal-fiber cement board
- Repair wall cracking
- Jointing between concrete slabs

## TECHNICAL DATA

| Item   | Standard   | SPEC      | ULTRA FLEX |
|--|------------|-----------|------------|
| Tack Free Time : min   | ASTM C697  | 25 - 40   | 35         |
| Tensile Strength : MPa   | ISO 37     | 1.0 - 1.5 | 1.05       |
| Elongation at break : %  | ISO 37     | 400-600   | 561        |
| Bonding Strength (3 Days) : MPa<br>* Wood - Fiber cement board | -          | 2.0 - 4.0 | 2.69       |
| Shore A hardness   | ASTM C 661 | 25 - 30   | 28,5       |

## INSTRUCTION

- Applied Ultra Flex to the properly prepared substrate directly from package.
- Uniformly distributed by notched trowel.
- Press the wood flooring / Metal-gypsum board / Metal-fiber cement board until same level.
- The elements can then be joined together using a hammer and an impact block and/or rubber mallet.
- Cleaning, uncured adhesive remaining on the wood flooring surface must be removed immediately with a clean cloth.



## RECOMMENDATION FOR USE

- For the best result, finish the whole sausage after opened. Remaining in the sausage, keep it tightly and avoid moisture in atmosphere.
- One year after manufacturing date when stored unopened in dry.
- 24 m. / cartridge, dimensions of nozzle 5 mm.

## PACKAGING

- 600 ml / sausage
- 20 sausages / box

## COMPANY CONTACT

**Noritake SCG Plaster CO., LTD.**  
 32 Moo7, Nongplakradi Road,  
 Nongpling, Nongkhae District,  
 Saraburi 18140 THAILAND

 +66 36 373578 - 82

 +66 36 373577

Website : [www.noritake-scg.com](http://www.noritake-scg.com)

## COLOR

