

ELEPHANT FireBloc



Fire Resistant Board



The Siam Gypsum Industry (Saraburi) Co., Ltd.
A member of USG Boral Building Products



ELEPHANT
Gypsum Board



FireBloc gypsum board encased with a specially designed compressed pink paper consisting of special fiber components that enhances its strength. Capable of fire resistance rating from 1 to 4 hours.

FireBloc gypsum board can be applied to all areas of house, office, or industrial buildings wherever fireproofing is needed.

Properties

- ◆ Consisting of fiberglass and fire resistant components in its core reinforcing it with more strength and fire resistant properties.
- ◆ Designing for fire resistance system up to 4 hours.
- ◆ No health hazard and environmental friendly. It can be recycled.

Standards and Tests

- ◆ ASTM E119

Usage Area

- ◆ High-rise building interior wall.
- ◆ Hotel, Factory sectors.
- ◆ Fire exits, Elevators and Shaft walls.
- ◆ Steel structure encasements and any areas with a high chance of fire exposure.
- ◆ Vaults.



Type	Size	Thickness (mm.)	Tapered Edge	Average Weight/Unit (Kg)	Average Weight (Kg/m ²)
Metric	1200x2400 (mm.)	12	✓	32.3	11.2
		15	✓	38.6	13.4
Imperial	4'x8' (ft.)	12	✓	33.3	11.2
		15	✓	39.8	13.4

