



MONTANIA WHITE SKIM COAT



Allow extra thin layer
(1-3 mm.).



Super smooth texture superior
than other types of plaster.



Perfectly cover hairline
cracks and bubbles.



Easy to apply.



WHITE SKIM COAT

Product Details

Ideal for smooth finishing on plastered wall, concrete wall, and other types of walls with extra smooth surface.

Outstanding Features :

- Allow extra thin layer (1-3 mm.).
- Super smooth texture superior than other types of plaster.
- Perfectly cover hairline cracks and bubbles.
- Easy to apply.

Net Weight 25 kg.

Usage Recommendations :

- More water should not be added after the creamy texture start to dry.
- All plastering tools must be cleaned with water before using

Application Area : Bag

12-15 sqm. for 1-3 mm. Layer thickness.

Application Method :

1. Mix 1 bag of product with 8-10 liters of clean water.
2. Gradually mix and stir the ingredients using mixer drill until well dissolved into thick cream and ready for use.

Suggestion :

- The working area should be airy.
- Suitable usage temperature is between 15 °C - 40 °C
- Refrain from further coating with oil paint as it may result in paint peel-off.
- Prevent dust-related hazards when using sandpaper for coated wall polishing.

TECHNICAL DATA

TEST ITEM	UNIT	SPEC	RESULT
Water/Powder	%	35	35
Mixing Time	min.sec	3.00	3.00
Final Setting Time	Hr.Min	5.30-6.30	5.30
Flow Slurry	mm	75 - 80	76
Slurry Density	g/cm3	1.3 ± 0.5	1.31
Dry Bonding Strength	Mpa	>0.25	1.13
Dry Compressive Strength	Mpa	>9	13.91

Shelf Life and Storage :

Unopened and undamaged bag in 12 months. Store in cool and dry area.

Manufactured by :
NORITAKE SCG PLASTER CO., LTD.

32 Moo 7, Nongplakradi Road, Nongpling, Nongkhae, Saraburi 18140 Thailand

Distributed by :

SCG International Corporation Co., Ltd.

1 Siam Cement Road, Bangsue, Bangkok 10800 Thailand

MADE IN THAILAND (MEMBER of ASEAN)

