

#### **SCG Smartwood**

SCG Smartwood is fiber cement product made from superior SCG Portland Cement, silica and special cellulose fiber through high standard process result in excellent properties.









Moss, mold, termite free



Fire safe



resistant




lasting



installing as wood

## **Extraordinary Beauty**

The designed SCG Smartwood teak and timber texture creates the natural look with better strength and durability but remains an easy workability as wood. The surface is coated with 'Color Loc Plus' Technology to lock the color molecule on SCG Smartwood for lifelong natural charm and less maintenance. SCG Smartwood can endure high temperature and reflect sunlight, prevents in-house overwhelming heat. Plus, the high quality coating also prevent mold and moss cover on surface, keep the true beauty lasting over time.





# SCG Wood Plank Natural elegance

Wood plank : Teak texture



Wood plank : Timber texture

Red Pradoo Wow Plus

Ivory



Ivory


Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	Usage (piece/sqm)
15	300 400	0.8	5.4 7.2	2.7 2.0
20	300 400	3.0	7.2 9.7	1.9 1.4

<sup>\*</sup>Wow Plus only available in 15 cm

SCG Wood Plank

# **Nordic series**

Timeless beauty







Nordic Pearl White




(cm)

20







(cm) 240 5.8 2.38 8.0 300

















Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	Usage (piece/sqm)
15	300 400	0.8	5.4 7.2	2.7 2.0
20	300 400	0.0	7.2 9.7	1.9 1.4



#### SCG Fascia Board

#### Fascia

Surface	Colour	Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	Usage (piece/sq m)	
Wood	Primer	10			9.3		
texture	Primer, Golden	15	400		14.2	0.25	
torttaro	Teak, Red Oak	20		1.6	19		
Connada	Cua a ma Duima a u	15	200		10.6	0.00	
Smooth	Cream Primer	20	300		14.3	0.33	

#### Primer

Red Oak

Golden Teak

Cream Primer

#### Fascia One Piece

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	Usage (piece/sq m)
23.5		1.8	18.3	
	300	2.4	18.4	0.33
23		1.8	15.8	
	400	1.0	21.5	0.25

#### One Piece - Cement

One Piece - Cream

Sure - Cement

Prompt - Primer

## SCG Eave Liner

Surface	Colour	Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	Usage (piece/sq m)
Smooth	Cement, Oak, Red Oak	7.5			2.7	4.44
SHOOLH	Cement	10			3.6	3.33
Wood texture	Cement Red Ruby (plus) Brown Teak (plus) Golden Teak (wow plus) Maka (wow plus) Pradoo (wow plus)	7.5	300	0.8	2.7	4.44

#### Cement

Oak

Red Oak

Red Ruby

Brown Teak

Golden Teak

Maka


Pradoo

## SCG Ceiling Border

Width (cm)	Length (cm)	Thickness (cm)		Usage (piece/sq m)
5	300	0.8	1.7	0.33

#### Brown Oak

Cement






## SCG Curve

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
10	100	1.2	1.9



## SCG Fence

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
7.5	7.5	12	5.4
10	400	1.2	7.3
10		1.6	9.7



	/idth cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
<u> </u>	7.5	300	1.2	4.1







# DECORATIVE MATERIAL





# Imprint the space with its own unique identity by our alternative decoration materials...




# Nothing is impossible.

SCG is an alternative decoration material which is created for designers to generate their ideas without limits. Its features let the designers include their ideas and make their own creativity, unleashing the imagination to make a special, novel and unique designs.

Our materials include fiber cement consisted of SCG Portland cement, pure silica and cellulose fibers. It is manufactured with CTRUSION (SCG's copyright) capable to be formed as desired by using molds specifically designed by professional engineer. As such, the product

has finely detailed and exquisite shape and dimension. The entire panel have completely homogeneous texture, thus superior or density to general cement fiber product. Given that, SCG is stronger, more durable and more suitable for various types of works. Moreover, We always find allternative materials to match with what's customers' design appropriately that would satisfy their aesthetic sense as we are solution provider. SCG aims to provide a high standard quality with a completed solution in order to serve all customer wants offering design consultant service till to installation quide and warranty. We want to deliver the best experience using SCG materials and solution.

SCG also has 3 additional groups of products for unleashing your limited imagination whether they will be anexterior or interior wall (WALL); shading louver, trellis, beautiful and eye-catching baseboard (LATH AND TRIM); and floor materials (FLOOR).



# **SCG Modeena**

#### **Striking Organize Pattern**

Stunning the facade and interior wall with a striking organize pattern both systematic and intricate pattern, represent in natural wood look moreover, in modern style.

Also make it more well neat with a none screw installation.




<sup>\*</sup>Above information is M1 only, for other series please see in product directory (P.29)

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
30	300	1.8	14.8

\*Above information is L1 only, for other series please see in product directory (P.29)









# **SCG Lap Siding**


Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
18			6.98
00.0	300	1	9.44
23.6			9.31

# SCG Decorative wall: Groove

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)
120	280	0.8	40

# SCG Decorative wall: Rustic

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)		
120	240	0.6	25.69		



LATH &TRIM

# Create your own UNIQUENES


# **SCG Line**

## **Unrivaled Artficial Timber**

Unlimited the aesthetic imagination wood panel with superior durable, adaptable wood stick. And make it more stylish with a timber patterm paint finishing.

	Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)		
,	5	300	2.5	5.7		





# **SCG C-Channel**

#### **Unrivaled Artficial Timber**

Supass all the steel material restrictions to express the industrial look of steel with a genuine virtual steel decoration material.

More affordable, easier installation moreoverwith its solid durable form.

Width (cm)	Length (cm)	Height (cm)	Thickness (cm)	Weight (kgs/piece)
15	300	5	1.2	14
22.3	300	5	1.2	18.3
30	300	5	1.2	21.1

Width 15 cm.

Width 22.3 cm.

Width 30 cm.

Width (cm)	Length (cm)	Height (cm)	Thickness (cm)	Weight (kgs/piece)
22.3	300	8	1.2	22.1
30	300	8	1.2	28.1

C-Plus Width 22.3 cm.


C-Plus Width 30 cm.



# SCG Trim Standard Neat Ornament


Well neat the space, fulfill the surface with a linear trimming decorative material. Comes with a groove detail profiling to ensure the most efficient use and worry-free to design a picturesque wall.

Or pave a way to new possibilities of wall decoration, creating a bold new, eye-catching look by installing SCG Trim (baseboard) inside out, which reveals its outstanding and unique concave parts or cutting and using as an air ventilation block, creating a wall with the distinct and stunning shape.



Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)		
10	300	5	12.8		
15	300	5	16.8		
20	300	5	22.3		





# **SCG T-Clip Floor Plank**

Floor decoration with SCG T-Clip, a feel of nature warm. SCG T-Clip is installed by screwless and pre-painted T-Clip. Each panel is up to standard with its beautiful and durable paint, reducing installation time.

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)		
16	200	2.5	17.4		
20	300	2.5	22.6		

Color










Natural Beech


Mahogany



# **SCG Saver Floor Plank**

A different way to timber floor decoration with colored cement as your desires, SCG Saver which helps you save cost. A long-lasting paint can be achieved by sealer paint applied on timber texture.

Width (cm)	Length (cm)	Thickness (cm)	Weight (kgs/piece)	
10	300		11.3	
15		2.5	16.9	
20			22.6	



Product Group	Series	С	olor	Width (cm)	Length (cm)	Thickness (cm)	Weight (Kgs)	Usage (pieces/sqm)	Surface	Edges
				15	300		5.4	2.66		
				15	400		7.2	2.00		
	Timber	Cement		20	300	0.8	7.2	1.90		
				20	400		9.7	1.43		Non Tapered
				23	366	0.65	8.3	1.33	Timber	
				20	366*	0.75	9.6	1.33		
				15	300*		5.4	2.63		
	Timber - Tapered Edge			13	400*	0.8	7.2	2.00		
				20	300*		7.2	1.90		2 Side Tapered
				20	400*		9.7	1.43		
				15	300		5.4	2.66		
	Primer	Primer	SEE SEE VINE LES		400	0.8	0.8	2.00	Teak	
	i iiiiGi	Time		20	300		7.2	1.90	Teak	
				20	400		9.7	1.43		
		lvory		15	300		5.4	2.66		
				13	400		7.2	2.00		
				20	300		7.2	1.90		
				20	400		9.7	1.43		
	Classic			15	300	0.8	5.4	2.66		
Wood Plank		Oak Red		13	400		7.2	2.00		
				20	300		7.2	1.90		
				20	400		9.7	1.43		
		Sky		15	300		5.4	2.66	Teak	
				15	400		7.2	2.00		
				15	300		5.4	2.66		
		Golden Teak		10	400		7.2	2.00		Non Tapered
		Goldon Tour		20	300		7.2	1.90		Non Tapered
	Natural			20	400	0.8	9.7	1.43		
				15	300		5.4	2.66		
		Red Maka		10	400		7.2	2.00		
		. Iou mana		20	300		7.2	1.90		
				20	400		9.7	1.43		
				15	300		5.4	2.67		
		5 .5 . 5		15	400		7.2	2.00		
		Red Ruby Plus	Carlo	20	300		7.2	1.90		
	Special Plus			20	400	0.8	9.7	1.43	Timber	
				15	300	0.0	5.4	2.67	71111001	
		Brown Teak Plus		15	400		7.2	2.00		
		2.0.771100011100		20	300		7.2	1.90		
				20	400		9.7	1.43		

Product Group	Series	Co	olor	Width (cm)	Length (cm)	Thickness (cm)	Weight (Kgs)	Usage (pieces/sqm)	Surface	Edges
					300		5.4	2.67		
		Golden Teak Wow Plus		15	400		7.2	2.00		
				20	400		9.7	1.43		
	MACONA DI		15	300		5.4	2.67	Timber		
	WOW Plus	Maka Wow Plus			400	0.8	7.2	2.00	-	
				20	400		9.7	1.43	-	
		D 10 1 W 5		15	300		5.4	2.67	-	
		Red Pradoo Wow Plus			400		7.2	2.00	-	
				20	400*		9.7	1.43		
				15	300 400	_	7.2	2.67	_	
		Golden Teak			300	_	7.2	1.90	_	
				20	400		9.7	1.43	Timber	
					300	0.8	5.4	2.67		
	Cool Dive	Diatious Crov		15	400		7.2	2.00		
	Cool Plus	Platinum Grey			300		7.2	1.90		
				20	400	_	9.7	1.43	-	Non Tapered
					300		5.4	2.67		
		Pearl			400		7.2	2.00	Teak	
Wood Plank		Night Grey		15	300		5.4	2.67	- Iean	
					400		7.2	2.00		
		Dooyl M/hito			240*	7.2	5.8	2.38		
		Pearl White			300*		7.2	1.90		
		Dark Anthracite			240*		5.8	2.38		
					300*		7.2	1.90		
					240*		5.8	2.38		
	Nordic Series	Silver Grey		20	300*	0.8	7.2	1.90	Timber	
					240*		5.8	2.38		
		Onyx Black			300*		7.2	1.90		
		Pine Nut Brown								
		Smoked Oak			300*		7.2	1.90		
	Craftman-Colonial	lvory		20	300	0.8	7.2	1.90	Teak	Lining Skirt Board Edge
	Craftman-New England	lvory		20	300	0.8	7.2	1.90	Teak	1 Side Square Lining

Product Group	Series	Cole	or	Width (cm)	Length (cm)	Thickness (cm)	Weight (Kgs)	Usage (pieces/sqm)	Surface	Edges
				10			9.3			
		Primer	1000	15			14.2			
				20		1.6	19		Teak	
	Wood Texture	Red Oak		15	400		14.2	0 05 (D) ( )		
Fascia				20			19	0.25 (Pieces/m)		
		Golden Teak		15 20		1.0	14.2 19	_		1 Side Tapered
		Caramel*		20	400		19	_		
				15		_	10.6		0 "	
	Smooth Texture	Cream Primer		20	300		14.3	0.33 (Pieces/m) Smooth		
	Prompt	Primer		23.5		1.8	18.3			
	One Piece	Cement		23	300	2.4	18.4	0.33 (Piocos/m)		
Fascia One Piece		Cream		23		2.4	10.4	0.33 (Pieces/m)	Smooth	
	Sure	Cement		23	300	15.8			1 Side Tapered	
					400	1.8	21.5	0.25 (Pieces/m)		
		Mahogany		23						
	Tapered Edge	Cement		7.5			2.7	4.44		
_		Oak		10	300		3.6	3.33	Smooth	
	Classic	Red Oak		7.5	300		2.7	4.44	omodii	2 Side Tapered
		Caramel*		7.0						
Eaves Liner	Timber	Cement			0.8					
		Golden Teak Wow Plus								
	WOW Plus	Maka Wow Plus						4.44		
		Pradoo Wow Plus		7.5	300		2.7		Timber	2 Side Eased
_										
	Special Plus	Red Ruby Plus								
		Brown Teak Plus								
		Oak								
Ceiling Border	Ceiling Border			5	300	0.8	1.7	6.67	Smooth	1 Cida Tanayad
		Cement								1 Side Tapered
				7.5			5.4	3.3		
Fence Plank	Fence Plank	Primer			400	1.2	7.3	2.5	Teak	
	1 GIICG I Idlik			10	400	1.6	9.7	2.5		2 Side Tapered
		Oolder Teel WOW								
Shading Plank	Shading Plank	Golden Teak WOW		7.5	300	1.2	4.1	4.44	Smooth	
	2	Primer			300	1.2		4.44	SHIOOH	1 Side Tapered

<sup>\*</sup> is Made to Order product

27

Product Group	Series	Color	Width x Length (cm)	Thickness (cm)	Weight (Kgs)	Usage (pieces/sqm)
	Classic	Cement	10 x 300	1.2	5	
Skirt Board	Classic	Primer				3.33
	Modern	Primer			5.4	
	Tread		27.5 x 120	2.5	13	3.03
Stair	Riser	Cement	18 x120	1.6	5.3	4.63
	Land		15 x 300	2.5	17	2.22

## SCG DECORATIVE MATERIAL DIRECTORY

Product Group	Series	Color	Width x Length (cm)	Thickness (cm)	Weight (Kgs)	Usage (pieces/sqm)
	Rustic	Cement	120 x 240	0.6	25.69	0.35
	Groove	Comon	120 x 280	8.0	40	0.30
		V1	18 x 300		6.98	2.08
	Lap Siding	V2	23.6 x 300	1	9.44	1.54
		V3	23.6 x 300	Į.	9.31	1.54
		K1	23.6 x 300		9.6	1.54
		M1	30 x 150		10.4	2.22
Decorative Wall		IVI I	30 x 300	2.5	20.8	1.11
		140	30 x 150	2.0	11.4	2.22
Decorative wall		M2	30 x 300		22.8	1.11
	Modeena	140	30 x 150		11.9	2.22
	Modeena	M3	30 x 300		23.8	1.11
			30 x 150	0.0	10.3	2.22
		M4	30 x 300	2.3	20.6	1.11
			30 x 150		12.3	2.38
		M5	30 x 300		24.6	1.18
	Modeena Lite	Lite 1	00 × 000	1.0	14.8	4 44
	Wodeena Lite	Lite 4	30 x 300	1.8	15.9	1.11
			15 x 300		14	2.22
	C Channel	Cement	22.3 x 300		18.3	1.49
			30 x 300	1.2	21.1	1.11
	C-Channel-Plus		22.3 x 300		22.1	1.49
Tuine	G-Griannei-Pius		30 x 300		28.1	1.11
Trim			10 x 300		13.3	3.33
	Trim	Cement	15 x 300	<i>E</i>	17.4	2.22
	111111	Cement	10 x 300	5	12.8	3.33
			15 x 300		16.8	2.22
	Line	Cement	5 x 300	2.5	5.7	6.67
	Decorative Floor	Cement	15 x 300	1.5	10.12	2.22
			10 x 300		11.3	3.33
	Saver	Cement	15 x 300		16.9	2.22
			20 x 300		22.6	1.67
Floor			10 x 300		9.73	3.33
FIOOI	Basic	Cream Primer	15 x 300	2.5	14.6	2.22
			20 x 300		19.45	1.67
		Natural Beech	20 x 300		22.6	1.67
	T-Clip	Mahogany	20 x 300		22.6	1.67
		Oak Brown	20 x 300		22.6	1.67

#### INSTALLING ACCESSORIES FOR SCG SMARTWOOD

Wood Plank	Interior	SCG Needle Point Screw 23 mm	<b></b>	500 pcs/box
	Exterior	SCG Self Drilling Wing Screw 28.5 mm	-	250 pcs/box
		· SCG C-Line	-10	1 strip
	Brick Walls	· SCG Brackets	200	60 pcs/box
	or	· SCG Needle Point Screw 38 mm		250 pcs/box
	Old Concrete Walls	with SCG Plastic Insert 37 mm	Edward .	250 pcs/box
		· SCG Self Drilling Screw 13 mm	Bitto	500 pcs/box
Fascia Board		SCG Self Drilling Wing Screw 32 mm	-	250 pcs/box
	Fascia	SCG Needle Point Screw 38 mm	\$	250 pcs/box
		Self Drilling Wing Screw 45 mm	Name and Address of the Owner, where the Owner, which the Owner, where the Owner, which the	Available in Typical Store
Eaves Liner/ Ceiling Border	Interior and Exterior	SCG Needle Point Screw 23 mm	- December	500 pcs/box
		SCG Self Drilling Wing Screw 28.5 mm	-	250 pcs/box

#### FINISHING ACCESSORIES FOR SCG SMARTWOOD

#### **SCG Coner Post Cement**

Use to cover inner and outer corners of Wood Plank

**Dimension**: 7.5 x 7.5 x 300 x 0.8 cm

Weight : 5.2 Kg
Color : Cement
Usage : 0.33 pcs/m



#### **SCG Acrylic Sealant**

To seal joints and cover screw heads for both external and internal

Size : 310 ml Weight : 0.5 Kg Color : White

Usage : 15-20 Sqm/tube



#### **SCG Acrylic Paint for Wood Plank**

100% water-based paint to finish screw heads or joints

Weight : 1 Kg

Color : Golden teak, Red maka, Ivory,

Red oak, Brown oak (for eaves liner)

Color type : Glossy

Usage : 7-10 Sqm/bucket



#### **SCG Acrylic Paint for Fiber Cement**

100% water-based transparent acrylic paint for any fiber cement wood

Weight : 3.5 Kg
Color : Cream primer
Usage : 60 Sqm/bucket

Weight : 3 Kg

Color : Natural beech, Mahogany,

Redwood, Dark oak

Color type : Glossy, Matt

Usage : 20-25 Sqm/bucket (2-3 rounds)

#### SCG Acrylic Paint for Stair Plank

Primer for coating before paint

Weight : 2 Kg
Color type : Brown
Usage : 10-15 Sqm/bucket

Acrylic paint for stair Plank

Weight : 3.6 Kg
Color : Redwood

Usage : 20-25 Sqm/bucket (2-3 rounds)

Shield gloss to cover the acrylic paint

Weight : 2 Kg
Color type : Clear Glossy
Usage : 20-25 Sqm/bucket



#### **SCG Acrylic Paint for Floor Plank**

100% water-based acrylic paint especially for Floor Plank. Resistant to scratch from walking.

Weight : 3.6 Kg

Color : Natural beech, Mahogany,

Dark oak, Redwood

Color type : Glossy, Matt
Usage : 20-25 Sqm/bucket

(2-3 rounds)



#### **HANDLING & STORING**




- Do not drag products from the pallet, as it may leave permanent scratch marks.
- The products must be carried by two people and held the product 30 cm from both end.
- Products can be lifted by width side only when they are in pack and must be lifted by narrow edge when unpack.



• Do not lift the products at the center as it may break.

#### **PRODUCT STORING**

- SCG Smartwood must be stored on a pallet or support with timber 1.5x3 inches every 60 cm on dry and levelled floor and covered with tarpaulin.
- SCG Smartwood should not be stacked higher than 1.5 m and must be stored vertically align.



#### PRODUCT PREPARATION BEFORE INSTALLATION

• Ensure that products are dry. To install products when they are wet may cause damages and bending.





**WARNING** 

Do not use these products as building structures, or parts of a deck or for any purposes that are not advised by SCG. When installing these products, installers must follow every step and criteria provided in the instruction manual and use tools that meet specific standards of the product manufacturer. Do not eat or swallow. Avoid inhaling wood dust generated from sawing, tapering, drilling and sanding. These products should not be installed in areas that are higher than 50 cm from the ground.



The products of SCG Smartwood are designed for working condition in Thailand. Any application or usage outside Thailand must follow and is considered to be responsibility of projects' architect, designer, construction supervisor and installer. These products contain dangerous chemicals. Do not eat, swallow, or touch your eyes. Use protection equipment that meets safe standards during tactical and technical operations. After the use, store it in a secure location and keep it out of children's reach. If experience skin irritation after touching the surface of the wood, wash the irritated area with clean water and seek medical help right away. If eat or swallow, avoid vomiting, drink plenty of water to abate the chemicals, and get medical help right away. All of the criteria for installation are of rudimentary steps for normal usage only, For more in depth specifications for installations and requirements for proper sites and conditions that materials can be used under, please read the standards of "allowable strength design" (ELT 1015-40) and criteria for designing building prescribed by the ministerial regulation No. 6 8.E. 2527, which is adopted from "building Control Act" B.E. 2522. Product installation manual is regularly updated. The architect, designer, construction supervisor, and installer shall verify the methods implemented follow the most updated installation manual on the website: https://www.scgbuildingmaterials.com/en/product/celling-wall

• Color shade may vary from real product due to production and printing process

